



SG 2810



PRODUCT INFORMATION

- **Operation:** chain
- **Range:** S - M
- **Fitting:** ceiling, wall, recess
- **Colours:** white RAL 9016 or anodised aluminum, special colours possible
- **Fabrics:** refer to Silent Gliss fabric collection


Features:

- Optimised light control
- Mono controlled
- Pull override protection
- Louvre width: 127 mm (standard), 89 mm
- Vertical Waves
- Bendable

10/2021/V1

SYSTEM SPECIFICATIONS

A. SYSTEM DIMENSIONS



127 mm louvres: 5 m
89 mm louvres: 3.8 m



40 cm



4 m






200 g per louvre

Max. system widths

	127 mm 89 mm	5 m 3.8 m
	127 mm 89 mm	4 m 3.1 m
	127 mm 89 mm	4 m 3.1 m

Stack sizes


										
		100	150	200	250	300	350	400	450	500
127 mm		27	35	42	50	57	65	72	80	87
		21	25	28	32	36	39	43	47	50
89 mm		29	40	50	60	69	80			
		20	25	30	35	39	45			

(cm)


(cm)

B. PROFILE


Profile and bending information



SG 2601
Profile




SG 2614
Recess profile



SG 2615
Recess profile




**C. HOW TO
MEASURE**



- A: System width
- B: System height
- C: Distance between floor and fabric
- D: Chain height
- E: Safety retainer SG 10731 min. 150 cm above floor

Light gap




FITTING

**A. FITTING
INFORMATION**



For detailed fitting information, visit the [Silent Gliss website](#).

Fixing points



B. CEILING FITTING

Bracket SG 2616




SG 2616
Bracket

Min. wall distance louvres	X mm
89 mm	65
127 mm	85
Vertical Waves 89 mm	115
Vertical Waves 125 mm	140


C. RECESS FITTING

Recess profile
SG 2615




Recess profile SG 2615 can not be bent!
One wedge SG 5118 per fixing point.
For detailed recess fitting, visit the Silent Gliss website.

Min. wall distance louveres	X mm
89 mm	65
127 mm	85
Vertical Waves 89 mm	115
Vertical Waves 125 mm	140




SG 2615
Recess profile




SG 5118
Wedge

Suspended ceiling /
recess profile
SG 2614 and hanger
SG 6268




Recess profile SG 2614 can not be bent!
One wedge SG 5118 per fixing point.
For detailed recess fitting, visit the Silent Gliss website.


Min. wall distance louveres	X mm
89 mm	65
127 mm	85
Vertical Waves 89 mm	115
Vertical Waves 125 mm	140



SG 2614
Recess profile




SG 5118
Wedge




SG 6268
Hanger

D. WALL FITTING


Smart Fix



Smart Fix SG 11201 - SG 11204 and bracket SG 2616:
Screw SG 10395 (M4x6) needed




Square Smart Fix SG 11211 - SG 11214 and bracket SG 2616:
Screw SG 10395 (M4x6) needed



Universal Smart Fix SG 11154 - SG 11156 and bracket SG 2616:
Screw SG 10492 (M4x8) needed

Smart Fix	X mm
SG 11201 / SG 11211	72
SG 11202 / SG 11212	92
SG 11203 / SG 11213	112
SG 11204 / SG 11214	142
SG 11154	102-130
SG 11155	132-160
SG 11156	182-210
Min. wall distance louvres	
89 mm	65
127 mm	85
Vertical Waves 89 mm	115
Vertical Waves 125 mm	140




SG 2616
Bracket




SG 10395
Pan head screw M4x6




SG 10492
Pan head screw M4x8




SG 11201
Smart Fix 80 mm




SG 11202
Smart Fix 100 mm




SG 11203
Smart Fix 120 mm




SG 11204
Smart Fix 150 mm




SG 11211
Square Smart Fix 80 mm




SG 11212
Square Smart Fix 100 mm




SG 11213
Square Smart Fix 120 mm



SG 11214
Square Smart Fix 150 mm




SG 11154
Universal Smart Fix 120 mm



SG 11155

Universal Smart Fix 150 mm






SG 11156


Universal Smart Fix 200 mm

SYSTEM OPTIONS

A. VERTICAL WAVES



3D Vertical Waves only applicable with 125 mm louvres.





Wall ending

A: Wavy edge

B: Straight edge

B. STACKING VARIATIONS



A: Single stack in one direction

B: Pair stack in two directions symmetrical

C: Pair stack in one direction asymmetrical

D: Pair stack in two directions asymmetrical

E: Multiple stacking in one direction symmetrical or asymmetrical

F: Centre stack

GENERAL NOTES

Dimensions

- Measurements are in mm except where indicated.
- Max. kg relates to fabric incl. accessories (bottom bars, etc.).
- Recommended distance floor / fabric: 20 mm.
- In order to determine system height (B), the smallest room height must be taken into account.

Fitting










- Installation by qualified fitter only.
- Number of brackets and fitting positions / fixing points vary depending on fitting surface, system weight, fabric make-up, screw / fixing type and obstacles.
- Qualified fitter must use appropriate screws / fixings for each situation.
- Profile lip if applicable to be installed to room side.
- Electrical installations must be carried out according to Silent Gliss wiring diagrams and conform to local regulations.
- Check space for cables and plugs!



Child Safety

- All relevant Silent Gliss systems correspond to child safety EN 13120.
- All parties involved must comply with EN 13120.










PARTS














A. STANDARD PARTS

	SG 2601 Profile
	SG 2604 Guide
	SG 2605 Top clip 127 mm
	SG 2610 End stop
	SG 2611 Stopper
	SG 2612 Brake
	SG 2616 Bracket
	SG 2620 Pilot runner
	SG 2623 Rotation element set 127 mm
	SG 2624 Rotation element set 100 mm
	SG 2627 Cover
	SG 2865 Bead chain connector ø 4.6 mm
	SG 2872 Bead chain plastic ø 4.6 mm
	SG 2888 Bottom link 127 mm

	SG 2892 Bottom weight 127 mm / 5"
	SG 10731 Child safety retainer set

B. OPTIONAL PARTS

	SG 2471 Bottom weight 127 mm
	SG 2473 Bottom weight 89 mm
	SG 2479 Bottom link 127 mm
	SG 2481 Bottom link 89 mm
	SG 2608 End stop
	SG 2614 Recess profile
	SG 2615 Recess profile
	SG 2618 Shaft
	SG 2625 Rotation element set 89 mm
	SG 2671 Bottom weight 89 mm
	SG 2672 Bottom weight 127 mm
	SG 2735 Holder
	SG 2813 Top clip 89 mm
	SG 2821 Spacer 63 mm / 2.5"

	SG 2881 Spring		SG 11203 Smart Fix 120 mm
	SG 2884 Bottom weight 89 mm		SG 11204 Smart Fix 150 mm
	SG 2889 Bottom link 89 mm		SG 11211 Square Smart Fix 80 mm
	SG 2890 Bottom weight 127 mm		SG 11212 Square Smart Fix 100 mm
	SG 3340 Cord/chain weight		SG 11213 Square Smart Fix 120 mm
	SG 5118 Wedge		SG 11214 Square Smart Fix 150 mm
	SG 6268 Hanger		
	SG 10395 Pan head screw M4x6		
	SG 10492 Pan head screw M4x8		
	SG 11154 Universal Smart Fix 120 mm		
	SG 11155 Universal Smart Fix 150 mm		
	SG 11156 Universal Smart Fix 200 mm		
	SG 11201 Smart Fix 80 mm		
	SG 11202 Smart Fix 100 mm		

